

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

DYNAMIC STREAMING MEDIA MANAGEMENT

Inventor(s):

Bret O'Rourke
Dawson Dean

ATTORNEY'S DOCKET NO. MS1-655US

10/26/2006 12:55:00

1 **TECHNICAL FIELD**

2 This disclosure relates to streaming multimedia content in networked
3 client/server systems.

4
5 **BACKGROUND**

6 When a client requests a piece of content such as digital video, audio, or
7 some other sampled content from a server, the client typically provides the global
8 address of the content in the form of a Uniform Resource Locator (URL). The
9 server then accesses the content and sends or "streams" it to the client as a
10 continuous data stream.

11 There are various file formats for streaming media content and composite
12 media streams. "Advanced Streaming Format" (ASF) is an example of such a file
13 format. ASF specifies the way in which multimedia content is stored, streamed,
14 and presented by the tools, servers, and clients of various multimedia vendors.
15 ASF provides a storage and transmission file format that encapsulates multimedia
16 data types. Images, audio, and video as well as embedded text (e.g., URLs),
17 graphic elements, and hyperlinks associated with elements on a Windows Media
18 Player ® interface are examples of items, or content that may be so encapsulated.
19 Such file formats provide for the synchronization of these objects within a stream.
20 Further details about ASF (also known as "WINDOWS Media Container Format")
21 are available from Microsoft Corporation of Redmond, Washington.

22 Regardless of the streaming file format used, an individual data stream
23 contains a sequence of digital data sets or units. The units represent an image,
24 sound, or some other stimuli that is perceived by a human to be continuously
25 varying. The client renders the units individually, in sequence, to reproduce the

1 original stimuli. For example, an audio data stream includes a sequence of sample
2 values that are converted to a pitch and volume to produce continuously varying
3 sound. A video data stream includes a sequence of digitally specified graphics
4 frames that are rendered in sequence to produce a moving picture.

5 In the simplest case, the client requests a single streaming media file, to
6 play a single piece of content such as a single song or a single video.
7 Alternatively, a client may request a playlist file that includes references to a
8 number of individual streaming media files, or content.

9 Each playlist file contains information such as whether to play certain
10 pieces of content more than one time, which pieces of content to play, the order in
11 which to play referenced content, and the like. Playlist files contain references to
12 one or more media streams and describe how pieces of media are combined.
13 Playlists do not contain the actual media data, but rather references to the media
14 data. As a result, playlist files are typically small, generally only containing text,
15 and are generally easy and computationally inexpensive to modify. References to
16 a single piece of media may appear in many playlist files.

17 Table 1 shows an example of a simple playlist.
18
19
20
21
22
23
24
25

TABLE 1
EXAMPLE OF A SIMPLE PLAYLIST

```
<ASX version = "3.0">
<Title>Title</Title>
<Entry><Ref href = "mms://nserver/content/title1.asf" /></Entry>
<Entry><Ref href = "mms://nserver/content/title2.asf" /></Entry>
<Entry><Ref href = "mms://nserver/content/title3.asf" /></Entry>
<Entry><Ref href = "mms://nserver/content/title4.asf" /></Entry>
</ASX>
```

Playlist referenced media content can be stored on a Windows Media ® server (e.g., <mms://ServerName/Path/FileName.asf>), a broadcast multicast (e.g., <http://WebServerName/Stations/kxyz.nsc>), a broadcast unicast that is accessed from a publishing point (e.g., <mms://ServerName/PublishingPointAlias>), on a Web server e.g., <http://WebServerName/Path/Filename.asf>), on a network share (e.g., <file://\\ServerName\\Path\\Filename.asf>), on a file on a local hard disk drive, and/or the like.

Playlist files have the effect of combining several individual pieces of content into one single complex piece of content, and they are incredibly important to providers of streaming media. They allow content providers to combine advertisements with other content, and therefore build a business based on advertising revenue. They allow Internet radio stations to create a playlist of broadcast songs. They also allow providers to brand their content by attaching previews or radio-station identifiers before or after the content.

For example, if the playlist is a client-side playlist, a script command may be sent to the client in a data stream to instruct Windows Media Player ® to cut

1 away from the stream and play other predetermined streams or files according to
2 predetermined playlist/metafile specified scripting in the client-based metafile.
3 This scripting technique can be used for predetermined/specified ad content
4 insertion. To illustrate this, consider that during a live Internet broadcast of a ball
5 game, a script command can be sent at the beginning of every commercial break
6 that instructs each client (e.g., a Windows Media Player ®) to play commercials
7 that are already identified in their metafile. When clients finish playing the
8 commercials, scripting in the metafile instructs each client to cut back to the live
9 broadcast.

10 Playlists are implemented either on a client or on a server such as a
11 WINDOWS Media ® server. When the client implements a playlist, the playlist
12 is typically downloaded from a server such as a Web server, a file server, and/or
13 the like. The client interprets the playlist file to present a series of requests to one
14 or more servers to access at least a portion of the content represented in the
15 playlist. A server is generally not aware that the client is requesting content that is
16 referenced in a client-side playlist file. This is because use of a client-side playlist
17 is indistinguishable from a client communicating a number of requests to the
18 server to play several different pieces of content one after the other.

19 Server-side playlists are maintained by a server and are not downloaded to
20 a client. To access the content represented by a server-side playlist, a client
21 typically selects a URL that identifies a server and a particular playlist. In
22 response, the identified server interprets the playlist to stream the content
23 referenced by the playlist to a client, one piece of content at a time.

24 Both clients that implement client-side playlists, and servers that implement
25 server-side playlists expect a playlist to be in a predetermined fixed data file

1 format. This is because the playlist must be interpreted, or parsed. To accomplish
2 this, such clients and servers typically include a playlist interpreter that can parse a
3 particular playlist data format. If a playlist is not in the right data format, the
4 server's playlist interpreter will not be able to parse/understand the content of the
5 playlist.

6 Such a fixed data file format requirement for representing playlists creates a
7 significant problem. Different content providers will often prefer different playlist
8 data formats, and therefore will use different types of playlist interpreters or
9 servers. In many cases, these interpreters are able to recognize and interpret only a
10 single format. This is a problem for a provider that desires to use a different
11 format because the provider is typically forced to choose either a non-preferred
12 format or a non-preferred interpreter. It also makes it difficult for a provider to
13 simultaneously use two or more different playlist formats.

14 Referring to Fig. 1, there is a block diagram that illustrates the use of a
15 fixed format playlist 104 to represent media content to stream to a client.
16 Streaming data server 102 accepts a fixed format playlist 104. The fixed format
17 playlist must represent its referenced media content in the fixed format expected
18 by server 102. If it is not in the expected fixed format, the content referenced by
19 the fixed format playlist 104 cannot be interpreted, and thus, cannot be streamed
20 by the server to client 110.

21 There are yet other problems associated with traditional systems and
22 procedures for streaming content using playlists. For example, there is generally
23 no way to impose a policy with respect to the content represented in a playlist
24 without modifying the playlist itself.
25

1 This is a problem because policy can change over time and content that
2 may have been contrary to a first policy may be allowable with a second policy. If
3 an original playlist is modified to meet the requirements of the first policy, then
4 the original playlist may need to be regenerated to recapture the excised content to
5 meet the second policy. In addition, modifying a playlist generally requires that
6 an administrator disable the playlist interpreter or server. This is a significant
7 problem for content servers—continuous, uninterrupted availability is an
8 important characteristic to most providers.

9 There are any number of scenarios that could require the regeneration or
10 versioning of playlists to meet the imposition of policy requirements. Such
11 playlist regeneration and versioning tasks could be very burdensome to program
12 directors, system administrators, and the like.

13 Yet another problem associated with traditional systems and procedures for
14 streaming data to a client using server-side playlists is that it is not feasible to
15 stream new content in the middle of other content that is already streaming to a
16 client. This is because generating a new streaming media file is computationally
17 very expensive. It means compressing video and/or audio data. For example, to
18 insert an advertisement into the middle of a movie, a new digital movie with the
19 advertisement in the middle of it would need to be created. This is not a practical
20 solution. Ideally, one could stream new content in the middle of other content that
21 is already streaming to a client without needing to regenerate a new streaming
22 media file.

1 **SUMMARY**

2 The described subject matter provides various implementations to stream
3 media content. In one aspect, a first playlist having a non-canonical data format is
4 accessed. One or more playlist translator components translate the non-canonical
5 data format of the playlist into a different playlist having a canonical data format.
6 The translation is performed in a manner that is independent of any modification
7 of the non-canonical data format playlist. The content referenced by the different
8 playlist having the canonical data format is streamed.

9 In this manner, media content providers are not required to generate playlist
10 files in any one particular data file format. Rather, a content provider is able to
11 generate a playlist in any preferred data file format, independent of a streaming
12 media server's playlist interpreter's fixed data file format requirements.

13 ~~In one implementation, a policy is imposed on the content referenced by the~~
14 ~~canonical data format playlist by one or more playlist transformer components .~~
15 ~~Although imposing the policy on the canonical data format playlist may result in~~
16 ~~modification of the playlist, the policy imposition is performed in a manner that is~~
17 ~~independent of any modification to the non-canonical data format playlist.~~

18
19 **BRIEF DESCRIPTION OF THE DRAWINGS**

20 Fig. 1 a block diagram that illustrates the use of a single, fixed format
21 server-side playlist to stream media content to a client.

22 Fig. 2 is a block diagram that illustrates aspects of an exemplary system to
23 stream multimedia content.

24 Fig. 3 is a block diagram that illustrates further aspects of exemplary
25 streaming media server/client system.

1 Fig. 4 is a flowchart that illustrates aspects of an exemplary procedure to
2 manage and stream media content.

3 Fig. 5 is a flowchart that illustrates further aspects of an exemplary
4 procedure to manage and stream media content.

5 Fig. 6 is a block diagram that illustrates aspects of an exemplary
6 environment to stream multimedia content.

7 8 **DETAILED DESCRIPTION**

9 The following description sets forth a various implementations of subject
10 matter that incorporates features recited in the appended claims. The
11 implementations are described with specificity to meet statutory requirements.
12 However, the description itself is not intended to limit the scope of this patent.
13 Rather, the inventors have contemplated that the claimed subject matter might also
14 be embodied in other ways, to include different elements or combinations of
15 elements similar to the ones described in this document, in conjunction with other
16 present or future technologies.

17 18 **Exemplary System for Playlist and Streaming Media Management**

19 Fig. 2 is a block diagram that shows aspects of an exemplary system 200 to
20 dynamically manage and stream multimedia content. The exemplary system is
21 only an example of a suitable computing environment to implement the described
22 inventive subject matter and does not suggest any limitation as to the scope of the
23 subject matter. The system includes a multimedia client/server 210 such as a
24 general purpose computer, a server computer, a Windows Media ® server, and/or
25 the like.

1 The multimedia client/server device 210 is coupled across a network 232 to
2 one or more other devices 238 such as a personal computer, a server computer,
3 and/or the like. The network can be any type of communication network such as
4 the Internet, an organizational intranet, a local-area network (LAN), private wide-
5 area networks, and/or the like.

6 The multimedia client/server device 210 includes a processor 212 that is
7 coupled to a system memory 214. The system memory includes any combination
8 of volatile and non-volatile computer-readable media for reading and writing.
9 Volatile computer-readable media includes, for example, random access memory
10 (RAM). Non-volatile computer-readable media includes, for example, read only
11 memory (ROM), magnetic media such as a hard-disk, an optical disk drive, a
12 floppy diskette, a flash memory card, a CD-ROM, and/or the like.

13 The processor 212 is configured to fetch and execute computer program
14 instructions from program modules stored in application programs 216. Such
15 program modules include, for example, an operating system, and other program
16 modules such as a media player (e.g., a WINDOWS ® Media Player), a playlist
17 server component 218, one or more playlist translator components 220, one or
18 more playlist transform components 222, a playlist supervisory component 224.

19 The multimedia client/server 210 utilizes one or more of these
20 components 216 to process requests from a client 238 for streaming media
21 content. The requested media content is referenced in a playlist 228 that is stored
22 as a files in some type of computer-readable memory such as data 226 or in other
23 storage media 236. The multimedia client/server translates such a playlist 228 into
24 a different playlist 230 that is in a canonical data format. Thus, media content
25 providers are not required to generate playlist files 228 in any one particular data

1 file format. Rather, a content provider is able to generate a playlist 228 in any
2 preferred data file format, independent of any playlist data file format requirement.

3 Although, the canonical playlist data format can be one of any number of
4 different data file formats, in this implementation, the canonical data format is the
5 Synchronized Multimedia Integration Language (version. 2.0), referred to as
6 "SMIL". SMIL is an extension of the World Wide Web Consortium (W3C)
7 standard Extensible Markup Language (XML) file format. SMIL provides syntax
8 and structure to define both high-level instructions and data corresponding to the
9 content referenced by a playlist. The specification for SMIL is well understood in
10 the computing industry.

11 The content referenced by the canonical data format playlist 130 is either
12 streamed to a client 238, or alternatively, rendered/played, and or the like, by the
13 multimedia client/server itself to reproduce the original stimuli of the referenced
14 content.

15 In one implementation, the multimedia client/server 210 is connected to a
16 graphical user interface (GUI) to facilitate the examination and manual
17 manipulation of an actively streaming playlist 230 by an administrator.

18 Playlist server component 218, translator component(s) 220, playlist
19 transform component 222, and supervisory component 224 may either run (a) in
20 the same address space as the server component 218, or (b) as part of another
21 process on the device 210, or (c) on an entirely different computer than the
22 device 210.

23 In this implementation, components 218, 220, and data structure 230 are
24 Common Object Model (COM) objects. COM objects expose their functionality
25 through clearly defined interfaces. Each interface has one or more methods that

1 are invoked by other objects. Logically related methods are normally organized
2 into a separate interface. The COM protocol is well known, and design tools for
3 creating COM objects are widely available.

4 Fig. 3 is a block diagram that shows further aspects of the exemplary
5 system 200 of Fig. 2 to manage and stream media content. The playlist server
6 component 218 accepts requests from one or more clients 238 for one or more
7 different original playlists 228 that may be in any one of a number of possible
8 playlist data formats. In response, the playlist server locates the requested
9 playlist(s) 228, which reference various multimedia content such as Images, audio,
10 video, as well as embedded text (e.g., URLs), graphic elements, hyperlinks
11 associated with elements on a Windows Media Player ® interface, and/or the like.

12 Such playlist referenced content can be stored on a Windows Media ®
13 server (e.g., mms://ServerName/Path/FileName.asf), a broadcast multicast (e.g.,
14 http://WebServerName/Stations/kxyz.nsc), a broadcast unicast that is accessed
15 from a publishing point (e.g., mms://ServerName/PublishingPointAlias), on a Web
16 server e.g., http://WebServerName/Path/Filename.asf), on a network share (e.g.,
17 file://ServerName/Path/Filename.asf), on a file on a local hard disk drive, and/or
18 the like.

19 Playlist server component 218 has a data structure 230 that represents a
20 playlist that is internal to the multimedia client/server 210 of Fig. 2. The server
21 dynamically generates a respective internal playlist 230 to manage a data stream to
22 a client 238 whenever the server 210 receives a request from a client that
23 references a playlist 228. There is any number of internal data structures, or
24 internal playlists 230.

1 Within the playlist server component 218, the internal playlist 230 is
2 represented in a pre-defined, non-variable data format, which will be referred to
3 herein as a "canonical" data format. SMIL is an example of such a canonical data
4 format. The canonical format may or may not be the same format that is used in
5 the actual playlists 228 that are submitted to playlist server 218 for playing.

6 The playlist server component exposes a canonical application program
7 interface (API) to provide an interface for other program applications (e.g., see,
8 program applications 216 of Fig. 2) to manipulate the contents of the data structure
9 130. In one implementation the canonical API is a platform and language-neutral
10 interface such as the DOM interface that permits script to access and update the
11 content, structure, and style of the data structure 230.

12 Interface 310 is exposed by data structure 230 and includes the SMIL
13 interface and a dynamic override interface for providing dynamic control over
14 media content being streamed (or to be streamed) by the server. The SMIL
15 interface allows programmatic addition of media references to the internal
16 playlist 230 and deletion of media references from playlist 230.

17 In this implementation, the dynamic programmatic override control
18 interface 310 includes a "stream media now" interface command and a "stop
19 streaming media now" interface command. Upon invoking the stream media now
20 interface, which specifies a particular media content item, a program module (such
21 as supervisory component 224) will cause the server 218 to immediately stream a
22 specified media content item. If the server is streaming a content item at the time
23 that a stream media now interface command is received by the server, the server
24 will stop streaming the content item to begin streaming the newly specified
25 content item.

1 Responsive to invocation of the stop streaming media now interface, the
2 server 218 immediately stops streaming a media content item. If a particular
3 media content item is specified in the override command, the server immediately
4 stops streaming the specified media content item, otherwise, all media content
5 items that are being streamed are stopped.

6 Although, this implementation describes use of the stream media now and
7 stop media stream now override commands, the programmatic override control
8 interface 310 may include different interfaces, which upon invocation cause the
9 server to immediately stop a particular streaming action to perform a different
10 action.

11 In operation, the playlist server 218 obtains a playlist 228 in either the
12 canonical data format or in a non-canonical data format. A playlist 228 may be
13 obtained from a variety of sources. The playlist server component 218 then
14 converts or translates the received playlist 228 into the canonical format for
15 internal representation (as internal data structure 230) and interpretation.

16 To translate playlist 228, the playlist server component 218 provides the
17 playlist to a select one of the translator components 220 based on the data format
18 of the received playlist. For example, one particular translator component may
19 only recognize playlists 228 having a particular data format. In one
20 implementation, a playlist's corresponding data format is determined by evaluation
21 of the contents of the playlist, by the suffix of the playlist's file name, and/or the
22 like.

23 The selected translator component 220 translates the provided playlist 228
24 from its native data format into a playlist 230 having a canonical data format.
25 Specific details of how a particular translator component 230 parses a native data

1 format of the provided playlist 228 are up to the particular translator component.
2 For example, a translator component 220 may:

- 3 • Parse playlist files written in a particular version of the SMIL format .
- 4 • Parse a playlist that includes a list of the contents of a directory on a file
5 system.
- 6 • Parse a playlist file format such as a Windows ® Media Player file
7 format.
- 8 • Query an SQL database to retrieve a list of streaming media content
9 references before translating the information into a playlist 230.
- 10 • Parse a playlist and at the same time, insert an advertisement before a
11 reference to a piece of content, the advertisement been selected based on
12 a broad range of criteria, such as the identity of a user, the time of day,
13 or which other advertisements have played recently.

14 After parsing at least a portion of the provided playlist 228, the selected
15 translator component 220 translates the parsed information into the playlist 230 by
16 calling methods of interface 310. In this implementation, the SMIL interface
17 includes a portion of the interface 310. These methods provide for the insertion of
18 streaming media control instructions and corresponding data into an internal server
19 playlist 230. The translator components create the canonical playlist 230 by
20 repeatedly calling the appropriate methods of interface 310, to insert individual
21 instructions and data as they are translated from the parsed native data format of
22 the original playlist 228.

23 In this implementation, playlist server component 218 exposes a component
24 registration and/or installation interface (not shown) to allow a plurality of
25 translator components 220 to be registered and/or installed for use with the playlist

1 server 218. To install/register a translator component 220, an interface object or
2 some other software entity calls the appropriate method or methods of the
3 registration/installation interface, and identify the new translator 220 and the
4 playlist data format that the new translator is designed to support.

5 Each translator component 220 exposes a substantially identical set of
6 interfaces. Thus, once access to a translator component 220 has been provided to
7 server component 218, the server component can interact with that translator
8 component through the translator's implemented interfaces. Specifically, the
9 server component 218 can call any one of the individual translator components to
10 provide a native data format playlist 228 to the translator component. The selected
11 translator component in turn parses and translates the provided native data format
12 playlist, and then uses interface 310 of the playlist server to insert canonical
13 playlist instructions and data into data structure 230.

14 Accordingly, different or additional translator components 220 can be
15 added to the system 200 at any time. This, in turn, allows the system to receive
16 and execute playlists in various different formats, each of which is supported by
17 one of the translator components. If a new playlist format become available, a
18 corresponding translator component is added to the system, without having to
19 modify the code of the server component 218.

20 System 200 includes one or more transform components 222 that are
21 provided with playlist server component 218. A transform component is used to
22 impose a policy on the media content referenced by playlist 230. In operation,
23 these transform components use interface 310 to modify the internal playlist of
24 data structure 230 before it is executed. To notify the transform components that
25 the playlist are transformed, the server component generates an event with a

1 reference to the playlist. At least one subset of the provided transform component
2 receives the generated event to impose one or more policies with respect to the
3 content of the playlist.

4 Imposing a policy can result in a modification to the internal playlist 230.
5 Such modifications include removing a reference from the playlist, adding a
6 reference to the playlist, changing the order of references in the playlist, modifying
7 a reference in the playlist, and the like. This allows policies such as adding
8 commercial content, deleting references to adult material, and the like, to be
9 imposed to suit a particular user or other condition.

10 To illustrate this, consider that a playlist may be modified based on a
11 policy to contain personalized advertisements targeted at a particular user, or to
12 change a radio station playlist to reflect the time of day (jazz in the morning and
13 heavy-metal late at night). The same policy or another policy may modify a
14 playlist so that a radio station will not play a same song too many times within a
15 particular amount of time such as in a single hour, or the playlist may be modified
16 to remove adult content from the playlist.

17 The transform components 222 impose such policies on the playlist of data
18 structure 230 without requiring the modification of the original playlist 228.
19 Instead, only the internal, canonical representation 230 of the original playlist 228
20 is modified. Advantageously, this means that even though a particular policy may
21 change over time, the original playlists will not have to be modified or regenerated
22 to impose the particular policy. Another advantage is that a transform component
23 need only be designed to recognize a single file format, the canonical data file
24 format of a playlist (regardless if it is a data format of playlist 228 or 230). In this
25 manner, regardless of the particular file format of an original playlist 228, and as

1 long as there is a corresponding translator component 220 to translate the original
2 playlist into the canonical data format, a policy may be implemented with respect
3 to the content of the original playlist.

4 Translator component(s) 220, playlist transform component 222, and
5 supervisory component 224, may invoke at least one portion of interface 312.
6 Interface 312 allows a playlist to be manipulated, or modified to follow an
7 arbitrary sequence of events—a sequence of events that is not constrained by the
8 data format of a playlist 230. Such modifications include, for example, inserting a
9 new reference into a playlist, deleting a reference from the playlist, moving a
10 reference from the first location in the playlist to a second location in the playlist,
11 switching to a different source of streaming media content, switching between live
12 broadcast feeds, and/or the like.

13 Such a canonical playlist 230 interface 312 provides a substantial advantage
14 over traditional procedures to stream media content referenced by server-side
15 playlists because it provides means for an external entity such as a computer
16 program to cause the server component 218 to follow a sequence of actions that
17 cannot typically be described in the data format of the playlist 230. Such actions
18 include, for example, changing between arbitrary sequences of live camera feeds,
19 and the like. In this example, the data corresponding to the live camera feed does
20 not need to be in a canonical data format because the server component 218 is
21 aware of the source and format of the switched media content.

22 In one implementation, the system 200 of Fig. 2 includes a supervisory
23 component 224 to control the sequence of streams communicated from the server
24 component 218 to a client 238 by manipulating the contents of the playlist 230.
25 This can be performed using any arbitrary determination/computation.

To control the sequence of streams, the supervisory component 224 periodically calls a particular function/method of interface 312 to set a next content item for the server component 218 to stream. If the method is not called, then the server component continues to execute a sequence of instructions from a data stream in the playlist 230 that was most recently played, if any.

Moreover, through the use of interface 312, the supervisory component could cause the server component to: (a) begin streaming content that is referenced at some other arbitrary position in the playlist; (b) stream the content scripted by an internal playlist 230; (c) insert a reference to content into the playlist sequence that was not before represented in the playlist; (d) interrupt the streaming of a particular media item to cause the server component to stream a different specified media item in place of the interrupted media item, later, if the method of interface 312 is not called, any sequence of events that is thereafter indicated by the playlist 230 will be performed, and/or the like.

Furthermore, the supervisory component 224 can use interface 310 to: examine the currently playing playlist 230, add and delete playlist instructions and data (including references to streaming media content), change an order of streaming media content presentation, dynamically start a particular media stream, dynamically interrupting, or stopping the streaming of one or more media streams, and the like.

Exemplary Procedure to Stream Media From a Server to a Client

Fig. 4 shows an exemplary procedure 400 of the system 200 of Figs. 2 and 3 to manage and stream media content. At block 410 the procedure initializes the multimedia client/server 210 of Fig. 2 by providing one or more translator

1 components 220, and one or more transform components 222. At block 412 the
2 procedure accesses a first playlist. In one implementation, this playlist access is
3 responsive to a request for streaming media content represented in the playlist
4 from a client device that is connected to a streaming media server that implements
5 server-side playlists. In another implementation, the playlist access is responsive
6 to user input at any computer that incorporates the features of multimedia
7 server/client 210 of Fig. 2.

8 At block 414, the procedure identifies the data format of the accessed
9 playlist. At block 416, the procedure determines a particular translator component
10 based in the identified playlist format (block 414). This is accomplished by
11 referencing respective translator component configuration data to identify
12 supported playlist formats. At block 418 the procedure generates a data
13 structure 230 of Figs. 2 and 3 that includes a canonical format playlist. At block
14 420, the procedure provides the accessed playlist (block 412) to the determined
15 translator component (block 416) for parsing and translating the accessed playlist
16 into a canonical data format. At block 422, the procedure (using interface 310 of
17 Fig. 3), stores the translated playlist (block 420), or its individual instructions into
18 the canonical data structure (block 418).

19 At block 424, the procedure imposes any policies on the translated, or
20 canonical playlist/data structure's referenced media content. At block 426 the
21 procedure streams the content referenced by the canonical data structure to a client
22 for playing/rendering. Alternatively, at block 426, the client/server 210 of Fig. 2
23 renders/plays the content referenced by the canonical data structure. The
24 procedure 400 continues at block 510 as shown in Fig. 5.
25

1 Fig. 5 is a flowchart that shows further aspects of an exemplary
2 procedure 400 of Fig. 4 to use server-side playlist components to manage and
3 stream multimedia content. At block 510, the procedure determines if the data
4 stream has been interrupted (e.g., in response to a request by a supervisory
5 component 224 of Fig. 2). At block 512, the data stream not having been
6 interrupted, the procedure continues with the implementation of any playlist
7 instructions. At block 514, the procedure determines if it has reached the end of
8 the playlist. If so, the procedure ends. Otherwise, the procedure continues
9 streaming the referenced data and is receptive to any requests to interrupt the data
10 stream as described above in reference to block 510.

11 At block 516, the data stream having been interrupted (e.g., in response to a
12 request by a supervisory component 224 of Fig. 2), the procedure processes the
13 interrupt, which may require the modifying the playlist, interrupting currently
14 streaming content to stream other specified content, and/or the like. At block 512,
15 the procedure continues to stream data (if any) that is referenced by the playlist
16 according to the playlist instructions.

17 18 **Exemplary Computer Environment**

19 The subject matter is described in the general context of computer-
20 executable instructions, such as program modules, being executed by one or more
21 conventional personal computers. Generally, program modules include routines,
22 programs, objects, components, data structures, etc. that perform particular tasks
23 or implement particular abstract data types. Moreover, those skilled in the art will
24 appreciate that the subject matter may be practiced with other computer system
25 configurations, including hand-held devices, multiprocessor systems,

1 microprocessor-based or programmable consumer electronics, network PCs,
2 minicomputers, mainframe computers, and the like. In a distributed computer
3 environment, program modules may be located in both local and remote memory
4 storage devices.

5 Fig. 6 shows a general example of a computer 630 that is used as a server in
6 accordance with the subject matter. Computer 630 is shown as an example of a
7 computer that can perform the functions of a multimedia client/server
8 computer 210 of Fig. 2. Computer 630 includes one or more processors or
9 processing units 632, a system memory 634, and a bus 636 that couples various
10 system components including the system memory 634 to processors 632.

11 The bus 636 represents one or more of any of several types of bus
12 structures, including a memory bus or memory controller, a peripheral bus, an
13 accelerated graphics port, and a processor or local bus using any of a variety of
14 bus architectures. The system memory includes read only memory (ROM) 638
15 and random access memory (RAM) 640. A basic input/output system (BIOS) 642,
16 containing the basic routines that help to transfer information between elements
17 within computer 630, such as during start-up, is stored in ROM 638.
18 Computer 630 further includes a hard disk drive 644 for reading from and writing
19 to a hard disk, not shown, a magnetic disk drive 646 for reading from and writing
20 to a removable magnetic disk 648, and an optical disk drive 650 for reading from
21 or writing to a removable optical disk 652 such as a CD ROM or other optical
22 media. The hard disk drive 644, magnetic disk drive 646, and optical disk
23 drive 650 are connected to the bus 636 by an SCSI interface 654 or some other
24 appropriate interface. The drives and their associated computer-readable media
25

1 provide nonvolatile storage of computer readable instructions, data structures,
2 program modules and other data for computer 630.

3 Although the exemplary environment described herein employs a hard disk,
4 a removable magnetic disk 648 and a removable optical disk 652, it should be
5 appreciated by those skilled in the art that other types of computer readable media
6 which can store data that is accessible by a computer, such as magnetic cassettes,
7 flash memory cards, digital video disks, random access memories (RAMs) read
8 only memories (ROM), and the like, may also be used in the exemplary operating
9 environment.

10 A number of program modules may be stored on the hard disk, magnetic
11 disk 648, optical disk 652, ROM 638, or RAM 640, including an operating
12 system 658, one or more application programs 660, other program modules 662,
13 and program data 664.

14 A user may enter commands and information into computer 630 through
15 input devices such as keyboard 666 and pointing device 668. Other input devices
16 (not shown) may include a microphone, joystick, game pad, satellite dish, scanner,
17 or the like. These and other input devices are connected to the processing unit 632
18 through interface 670 that is coupled to bus 636. Monitor 672 or other type of
19 display device is also connected to bus 636 via an interface, such as video
20 adapter 674.

21 Computer 630 operates in a networked environment using logical
22 connections to one or more remote computers, such as a remote computer 676.
23 The remote computer 676 may be another personal computer, a server, a router, a
24 network PC, a peer device or other common network node, and typically includes
25 many or all of the elements described above relative to computer 630, although

1 only a memory storage device 678 has been illustrated in Fig. 6. Computer 676 is
2 shown as an example of a computer that can perform the functions of a client
3 computer 238 of Fig. 2. The logical connections depicted in Fig. 6 include a local
4 area network (LAN) 680 and a wide area network (WAN) 682. Such networking
5 environments are commonplace in offices, enterprise-wide computer networks,
6 intranets, and the Internet.

7 When used in a LAN networking environment, computer 630 is connected
8 to the local network 680 through a network interface or adapter 684. When used
9 in a WAN networking environment, computer 630 typically includes a modem 686
10 or other means for establishing communications over the wide area network 682,
11 such as the Internet. The modem 686, which may be internal or external, is
12 connected to the bus 636 via a serial port interface 656. In a networked
13 environment, program modules depicted relative to the personal computer 630, or
14 portions thereof, may be stored in the remote memory storage device. It will be
15 appreciated that the network connections shown are exemplary and other means of
16 establishing a communications link between the computers may be used.

17 Generally, the data processors of computer 630 are programmed by means
18 of instructions stored at different times in the various computer-readable storage
19 media of the computer. Programs and operating systems are typically distributed,
20 for example, on floppy disks or CD-ROMs. From there, they are installed or
21 loaded into the secondary memory of a computer. At execution, they are loaded at
22 least partially into the computer's primary electronic memory.

23 The subject matter described herein includes these and other various types
24 of computer-readable storage media when such media contain instructions or
25

1 programs for implementing the steps described below in reference to Fig. 6 in
2 conjunction with a microprocessor or other data processor.

3 The subject matter also includes the computer itself when programmed
4 according to the methods and techniques described below. Furthermore, certain
5 sub-components of the computer may be programmed to perform the functions
6 and steps described below. The subject matter includes such sub-components
7 when they are programmed as described. In addition, the subject matter described
8 herein includes data structures, described below, as embodied on various types of
9 memory media.

10 For purposes of illustration, data, programs and other executable program
11 components, such as the operating system are illustrated herein as discrete blocks,
12 although it is recognized that such programs and components reside at various
13 times in different storage components of the computer, and are executed by the
14 data processor(s) of the computer.

15 16 **Conclusion**

17 The described subject matter provides a number of significant advantages
18 as compared to the prior art. For example, playlist authors can use and distribute
19 any playlist format as long as a corresponding playlist translator is supplied. Also,
20 the subject matter provides for the imposition of arbitrary content filters or policies
21 without requiring modification of the original playlist. Further, the system allows
22 an administrator to manually modify an actively streaming playlist according to an
23 arbitrary sequence determined by the administrator without modifying the original
24 playlist.

1 Although the subject matter has been described in language specific to
2 structural features and/or methodological operations, it is to be understood that the
3 subject matter defined in the appended claims is not necessarily limited to the
4 specific features or operations described. Rather, the specific features and
5 operations are disclosed as exemplary forms of implementing the claimed subject
6 matter.

7 To illustrate this, consider that although various program modules 216 and
8 data structure 230 of Fig. 2 were described as using COM, it is not necessary that
9 any program module or data structure be implemented as a COM object. Rather,
10 the modules and data structures could use some other technology, proprietary or
11 otherwise, to expose respective functionalities through a clearly defined interface.
12
13
14
15
16
17
18
19
20
21
22
23
24
25